



PG50-1-RGB



the base shape for 2 m cable



the base shape for connector

OPTICAL DATA

LIGHT SOURCE	LED	LIGHT COLOUR	see table MODEL PARAMETERS
LAMP LIFETIME	50000 h		

MECHANICAL DATA

DIAMETER	Ø 50 mm	HEIGHT L1	213 mm
HOUSING MATERIAL	ABS (silver)	HEIGHT L2	70 mm
WINDOW MATERIAL	PC (translucent)		

ELECTRICAL DATA


RATED OPERATIONAL VOLTAGE	24 V DC	WIRING	see table MODEL PARAMETERS
OPERATING VOLTAGE	18 ... 30 V DC	CURRENT	see table MODEL PARAMETERS

ENVIRONMENTAL CONDITIONS

DEGREE OF PROTECTION	IP20	OPERATING TEMPERATURE	-20 °C ... 50 °C
-----------------------------	------	------------------------------	------------------

PG50-1-RGB

WIRING DIAGRAM



MODEL PARAMETERS

Model	Light segments	Colour	L1	L2	Buzzer	Wiring	Current
PG50-1-RGB	1	RGB*	213 mm	70 mm	No	Connector	R.G.B: 70 mA
PG50-1-RGB-S	1	RGB*	213 mm	70 mm	Yes	Connector	
PG50-1-RGB-S/2M	1	RGB*	213 mm	70 mm	Yes	Cable, 2 m	

* possible colours: Red, Green, Blue, Yellow, Cyan, Magenta, White

Pin	Red	Green	Blue	Yellow	Cyan	Magenta	White
1/BN	✓			✓		✓	✓
2/WH		✓		✓	✓		✓
3/BU	✓	✓	✓	✓	✓	✓	✓
4/BK			✓		✓	✓	✓

APPROVALS

